

Material Specification

featuring Ordesa Basalt



Material Specification

ORDESA BASALT

Basalt is classified as 'igneous' resulting from volcanic activity and magma reaching the surface as lava. The material is charcoal grey in tone and generally uniform in both composition and character.

It is an extremely versatile material suitable for commercial or residential flooring but also in demand for driveways, courtyards, garden paving, pool surrounds and pathways. A variety of surface finishes accommodates the adaptability of the product to all of the above applications.

Material Type:

Basalt

Available Surface Finishes:



Honed




Sandblasted
& brushed



Tumbled

Available Tile Sizes:

600x300mm, 800x400mm tiles and pavers, with custom tiles sizes available upon request.



General Guidelines for Installation & Maintenance:

Adhesive: **CTA Eco Systems Opticure** or equally approved.
Note; Minimise risk of Efflorescence by use of **Efflock** as an additive to water when used at any stage of the install process.

Sealer: **Sealers Plus Gold +** or equally approved.
Dip Sealing (six sided) with **Sealers Plus Ultra Block** is applicable to areas exposed to water such as shower walls and floors, pool and pond coping. Note: Sealing on completion with **Gold +** is still a requirement. Suggested to be resealed every 1-2 years.

Colour Enhance: For a darker shade consider substituting Gold + with either **Lithofin Intensifier** or **Sealers Plus Enhance 'N' Seal**. Lithofin Intensifier results in a more subtle colour change, Enhance n Seal gives a considerably darker result. If in doubt we suggest to experiment on a sample prior to proceeding.

Grout Specification: Suggested **Ardex Midnight FG8** but client or designer to nominate colour. Note; that the entire surface of the tile is also to be grouted.

Suggested Contractors: Cleaning, Sealing and Buffing on completion by the below contractors:

Nano Worx

P: 0403 321 982

E: sales@nanoworx.com.au

W: www.nanoworx.com.au

Sealwerx

P: 0400 362 360

E: sealwerxwa@bigpond.com

W: www.sealwerx.com.au

For technical guidelines for external feature walls, paving, driveways or any other application, please contact our office for further advice.

